Model: Steelworx Octagonal Gazebo, 18' Model # OCGZ-18-SW

Manufacturing Mission: To provide all prefabricated components and installation instructions for a 18' octangonal gazebo (measured from eave to eave) free standing bolt together, tubular steel constructed shelter kit.

Design Criteria: Structure is typically designed for a 30 lb live load and a 95-100 mph wind load capacity. All structural members are ASTM A-500 U.S. grade B steel. Welded connection plates shall be ASTM A-36 hot rolled steel. All welding performed to latest AWS standards by ASTM Certified welders and provided in accordance to same.

Tubular Steel Columns and Beams: Standard column dimensions shall be $5" \times 5" \times 3/16"$ tubular steel welded to 5/8" base plate (footing design provided separately). Perimeter and interior support beams are $3" \times 5"$ to $5" \times 7"$ with a thickness between 1/8" and 3/16" based on location.

Roof: 24 Ga. pre-cut steel panels with Kynar 500 finish in a variety of colors with white underside. Standard roof slope is a 6/12 pitch with a eave height of 8'-0".


Frame Finish: All steel framework will undergo a three step powder coat application that begins with welded raw steel being sand blasted to a white condition to eliminate contaminates and oils. Then a zinc-rich primer is applied and baked at 400°F, followed by a corrosion protective TGIC Polyester powder coat, electro-statically applied and cured at 400°F. A large selection of standard colors are available.

Hardware: All structural hardware provided and to be A-325 or B7 as required.

Not Included: Concrete work of any kind, unloading of product and installation.


Additional Options:

- Flexibility of Design
 Such as: Height and Pitch
- Additional Engineering
- Variety of Colors
- Decorative Railings, Lattice, Braces, Trim, etc.
- Column Style Variations
- Lexan Wind Screens
- Tongue & Groove Wood Decking
- Asphalt Shingles, Standing Seam, Cedar Shake, or Clay Tile Roofing.
- · Site Furnishings and Accs.
- Solar Panels & Solar Lighting



FOOTING LAYOUT PLAN

SCALE: NTS



TUBULAR STEEL
HIP BEAM (TYP)

STEEL COMPRESSION
RING

TUBULAR STEEL
BEAM (TYP)

11-6"

FRAMING PLAN

SCALE: NTS

Steelworx Octagonal Gazebo - 18'

Model: OCGZ-18-SW

DESIGN SPECIFICATIONS



11800 East 9 Mile Road Warren, MI 48089 Office: (586) 486-1088 Fax: (586) 754-9130 Toll Free: (800) 657-6118 Email: info@coverworx.net www.CoverWorx.net